

AS251S

RS232 Serial Auto Switch (2 to 1)



AS251S allows 2 PCs to share 1 serial (RS232) printer. It is easy to install and needs no additional power supply.

Features

- No External Power required.
- Output Port Selectable.
- Transparent to the user.
- OS Compatibility: WIN98, WIN ME, WIN 2K and WIN XP.

Specifications

Connectors	
Input	2 x RS-232 DB-25 Female
Output	1 x RS-232 DB-25 Male
LEDs	
Input	2
Port Selection	Auto / Manual
Input Arbitration	First come first served
Function Key	Manual / Select
Cable Length	15 m [50'] (max.)
Timeout Selection	10 ~ 60 seconds
Power Consumption	AC9V:0.1W:0.46BTU/h Note: ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.
Environmental	
Operating Temperature	0 ~50°C
Storage Temperature	-20 ~ 60°C
Humidity	0~80% RH, NC
Physical Properties	
Housing	Plastic
Weight	0.05 kg (0.11 lb)
Dimensions (L x W x H)	9.30 x 7.70 x 2.55 cm (3.66 x 3.03 x 1 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.