

BP36V18AH

External Battery Pack for OL1500LV / OL1500HV



ATEN UPS External Battery Pack extends battery runtime when used with ATEN UPS systems. Users will have an extra time to save valuable data from any unexpected power shutdowns.

Note: When the battery pack is not in use, please recharge it for 4 ~ 6 hours every 3 ~ 6 months.

Specifications

Electrical	
Nominal Input Voltage	36V
Nominal Output Voltage	36V
Maximum Output Current (Total)	50A Max
Battery	
Battery Type	Sealed Lead-Acid
Battery Size	12V/9Ah
Battery Quantity	6
Physical Properties	
Rack Unit	2U
Dimensions (L x W x H)	43.80 x 38.00 x 8.60 cm (17.24 x 14.96 x 3.39 in.)
Weight	21.50 kg (47.36 lb)
Environmental	
Temperature (Operating / Storage)	0 – 40 °C/-15 – 45 °C
Humidity (Operating & Storage)	0 – 90% (non-condensing)
Elevation (Operating / Storage)	10,000 ft (3,000 m)/50,000 ft (15,000 m)
Certifications	
Certifications	UL,CE
Approvals	RoHS Compliant
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.