

## PE0316B

0U Basic PDU

PE0316B



ATEN's Basic PDU family is extended with 0U members containing 16 outlets and available in IEC socket configurations. The compact aluminum housing gives a sleek, yet robust look while minimizing installation space for work space efficiency. The Basic PDUs are tailored made for individuals who are in need of industrial-grade, easy-to-deploy power distribution unit in data centers, server rooms, and network wiring closets.

### Features

- Space saving – 0U rack mount design
- IEC outlet model
- Aluminum material
- Works with data centers, server rooms, and telecom equipment

# Specifications

|                                    |                                                                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Electrical                         |                                                                                                                                 |
| Nominal Input Voltage              | 100-240 VAC                                                                                                                     |
| Maximum Input Current              | 30A Max<br>(UL de-rated 24A Max)                                                                                                |
| Input Frequency                    | 50-60 Hz                                                                                                                        |
| Input Connection                   | NEMA L6-30P                                                                                                                     |
| Input Power                        | 7200VA(Max);<br>5760VA(UL de-rated)                                                                                             |
| Outlet Type                        | (16) IEC 320 C13                                                                                                                |
| Maximum Output Current (Outlet)    | 15A Max<br>(UL de-rated 12A Max)                                                                                                |
| Maximum Output Current (Bank)      | 20A Max<br>(UL de-rated 16A Max)                                                                                                |
| Maximum Output Current (Total)     | 30A Max<br>(UL de-rated 24A Max)                                                                                                |
| OPD(Overcurrent Protection Device) | Yes                                                                                                                             |
| Physical Properties                |                                                                                                                                 |
| Dimensions (L x W x H)             | 96.71 x 4.44 x 9.28 cm<br>(38.07 x 1.75 x 3.65 in.)                                                                             |
| Weight                             | 2.50 kg ( 5.51 lb )                                                                                                             |
| Power Cord Length                  | 10ft(10#)                                                                                                                       |
| Environmental                      |                                                                                                                                 |
| Temperature (Operating / Storage)  | 0 – 40°C / -20 – 60°C                                                                                                           |
| Elevation (Operating / Storage)    | 3000m                                                                                                                           |
| Compliance                         |                                                                                                                                 |
| EMC Verification                   | FCC Class A                                                                                                                     |
| Safety Verification                | UL, other by request                                                                                                            |
| Note                               | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



Note: (1) As there are many Basic PDUs, PE0324S (top) and PE0118S (bottom) are the respective 0U and 1U examples used here.

**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.