

## CS1732A

2-Port PS/2-USB VGA/Audio KVMP™ Switch



CS1732A 2 Port KVM Switch has built-in USB on each of the front and rear panels and audio signal connectors. It allows users to control the computer and peripheral devices via a signal console at ease.

### Features


- One USB console controls 2 computers and two additional USB devices
- 2 port USB Hub built in
- Dual interface supports computers with PS/2 or USB keyboards and mice
- Multiplatform support: compatible with all operation platforms PC (Windows, Linux and most others), Mac and Sun
- With speaker and microphone support
- [Bi-directional switching and flexible interoperability; switch permits independent PC, independent peripheral, and independent audio function, regardless of KVM switch focus](#)
- Auto PS/2 and USB interface detection
- Buzzer On/Off via hotkey
- Keyboard and mouse emulation for error free booting
- Computer selection via front panel pushbuttons and hotkeys
- Superior video quality - up to 2048 x 1536; DDC2B
- Firmware upgradable
- OS Support: Windows 2000, Windows XP, [Windows Vista](#), LINUX, Mac, Sun and FreeBSD
- SUN/Mac keyboard support and emulation\*
  - \*1.PC keyboard combinations emulate SUN/Mac keyboards.
  - \*2.SUN/Mac keyboards only work with their own computers

### Specification

Computer Connections	2
Port Selection	Hotkey, Pushbutton
USB Port / Audio Port Selection	Hotkey
Connectors	
Console Ports	2 x USB Type A Female (White) 1 x HDB-15 Female (Black) 1 x Mini Stereo Jack Female(Green) 1 x Mini Stereo Jack Female (Pink)

KVM Ports	2 x SPHD-15 Female (Yellow) 2 x Mini Stereo Jack Female (Green) 2 x Mini Stereo Jack Female (Pink)
USB Hub	2 x USB Type A Female (Black)
Firmware Upgrade	1 x RJ-11 Female (Black)
Power	1 x DC Jack
Switches	
Ports	2 x Pushbutton
Firmware Upgrade	1 x Slide
LEDs	
Online / Selected	2 (Orange)
USB Link	2 (Green)
Emulation	
Keyboard / Mouse	USB
Video	2048 x 1536; DDC2B
Scan Interval	1-99 seconds
Power Consumption	DC5V:0.94W:30BTU/h  Note: <ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul>
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20-60°C
Humidity	0-80% RH, Non-condensing
Physical Properties	
Housing	Metal
Weight	0.55 kg ( 1.21 lb )
Dimensions (L x W x H)	14.00 x 8.80 x 5.55 cm (5.51 x 3.46 x 2.19 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their  
 respective owners.