

KE6948AR

Rugged DVI-I Dual-Display KVM over IP Receiver



The ATEN KE6948AR is an industrial-grade KVM over IP receiver certified to IEC 60945 and IACS E10 standards, specifically engineered to meet DNV-GL requirements for mission-critical Maritime control rooms and data centers. This advanced solution enables secure, zero-latency remote access to computer systems over IP networks.

System Architecture for Remote Management

The KE6948A system consists of a high-performance IP-based transmitter ([KE6948AT](#)) connected to the computer and a receiver (KE6948AR) that provides console access from a separate location. It enables remote access via USB consoles (keyboard, mouse, and DVI monitor) over an intranet, allowing systems to be placed in secure, temperature-controlled environments away from users' workstations, with support for lossless, zero-latency video resolution up to 1920 × 1200 @ 60 Hz.

Flexible Connectivity and Long-Distance Extension

Equipped with both RJ-45 ports and SFP slots, the KE6948A can connect directly or via a LAN using copper or fiber cabling. By utilizing 1Gbps SFP fiber modules, transmission distances can reach up to 10 km. To ensure dependable service and uptime, it features dual power supplies for power redundancy.

Scalable Deployment and Matrix Integration

As an IP-based solution, the KE6948AR is highly versatile. It can function in point-to-point, point-to-multipoint, or multipoint-to-point configurations. When integrated with the [CCKM](#) (Matrix Manager), it transforms into a full multipoint-to-multipoint [KVM over IP Matrix](#) System for complex environments.

Centralized Management

Implementing the [CCKM](#) software unlocks advanced administrative features. This includes auto-detection of all KE devices on a subnet for fast installation, as well as centralized authentication and authorization. Administrators can easily define, switch, and share different connection types across the network.

Secure Access and Data Protection

Security is a priority, with support for AES 128-bit encryption and external authentication via LDAP, Active Directory, RADIUS and TACACS+. Additionally, with built-in OSD (On-Screen Display), RS-232 support, and Auto MDIX, the KE6948AR provides a cost-effective and convenient digital extension solution across any intranet.

Note: SFP modules ([2A-136G](#) / [2A-137G](#)) are sold separately. Contact your ATEN dealer for details.

Specifications

Connectors	
USB Port	2 x USB Type A Female (White)
Console Ports	2 x USB Type A Female (White) 2 x DVI-I Female (White) 1 x Mini Stereo Jack (Green) 1 x Mini Stereo Jack (Pink) 1 x DB-9 Male (Black)
KVM Ports	N/A
Power	2 x Lockable DC Jack (Black)
LAN Ports	1 x RJ-45 (Black) 1 x SFP Slot
Switches	
Reset	1 x Semi-recessed Pushbutton
Mode Selection	1 x Slide Switch (Extension, RS-232 Config)
LEDs	
10/100/1000 Mbps	1 x LED for RJ45 (10/100: Off, 1000: Green) 1 x LED for SFP slot (10/100: Off, 1000: Green)
Power	2 (Green)
Local	1 (Green)
Remote	1 (Green)
Power Consumption	DC12V:14.46W:110BTU/h Note: ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.
Video Resolution	Up to 1920 x 1200 @ 60Hz
Latency	< 5ms
Environmental	
Operating Temperature	-15–55°C
Storage Temperature	-20–60°C
Humidity	0–95% RH, Non-condensing
Physical Properties	
Housing	Metal
Weight	2.36 kg (5.2 lb)

Dimensions (L x W x H)	21.47 x 21.11 x 4.18 cm (8.45 x 8.31 x 1.65 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their
respective owners.