

## BC36V9AH

Internal Battery Pack for OL1500LV / OL1500HV



The ATEN UPS Internal Battery Pack comes with a hot-swap design, allowing uninterrupted operations during battery replacement to ATEN UPS systems. It ensures stable power supply and offers easy installation, bringing users hassle-free management to their power equipment.

Note: When the battery pack is not in use, please recharge it for 4 ~ 6 hours every 3 ~ 6 months.

**Specifications**

|                                   |                                                                                                                                 |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Electrical                        |                                                                                                                                 |
| Nominal Output Voltage            | 36V                                                                                                                             |
| Battery                           |                                                                                                                                 |
| Battery Type                      | Sealed Lead-Acid                                                                                                                |
| Battery Size                      | 9AH                                                                                                                             |
| Battery Quantity                  | 3                                                                                                                               |
| Physical Properties               |                                                                                                                                 |
| Dimensions (L x W x H)            | 25.77 x 21.37 x 6.66 cm<br>(10.15 x 8.41 x 2.62 in.)                                                                            |
| Weight                            | 8.10 kg ( 17.84 lb )                                                                                                            |
| Color                             | Black                                                                                                                           |
| Environmental                     |                                                                                                                                 |
| Temperature (Operating / Storage) | Operating: 32 – 104 °F (0 – 40 °C)<br>Storage: -15 – 45 °C                                                                      |
| Humidity (Operating & Storage)    | 0–95%                                                                                                                           |
| Elevation (Operating / Storage)   | Operating: 0-10,000ft (0-3,000meter)<br>Storage: 0-50,000ft (0-15,000meter)                                                     |
| Note                              | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

**ATEN International Co., Ltd.**

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their respective owners.