

2L-2406

Cable VGA de 6 M



Este cable VGA está diseñado para proporcionar una conexión VGA de alta calidad, ideal para aplicaciones de alta resolución de hasta 1920 x 1200. Este cable de vídeo VGA, con una construcción muy duradera, elimina el efecto de imágenes fantasma y difusas, lo que garantiza a los usuarios experiencias de A/V de la máxima calidad.

Características

- Optimizado para la transmisión de señal analógica
 - Cable VGA con entrada hembra y salida macho de 15 patillas
 - Radio de flexión: 90°*
 - Material apantallado exterior: Cinta Al Mylar
 - Conforme con la directiva RoHS
 - Compatible con los productos VGA de ATEN
- Nota:* Oscila 1000 veces en ángulos de +/- 90 grados a una frecuencia de 30 veces por minuto

Especificaciones

Conductor	
Material	Cobre estañado
Diámetro del conductor	30 AWG
Enfundado	
Material	Funda: PVC Apantallado: AL-Mylar
Conectores	
Vídeo	1 x HDB-15 macho (Azul)
Longitud del cable	6 m



Simply Better Connections

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their
respective owners.