

## RCMA200SA

RCM Adapter Module with 60-pin and RS-232 Control for UF200SA Server



The RCMA200SA, the industry's first adapter module, is designed to work with ATEN [KA7174](#) and RCM series multi-port products (such as [RCM816](#)), which allows easy access to UF300 and UF200SA wafer prober from both the local and remote consoles. It also supports a virtual keyboard to facilitate installation and production line operations.


### Characteristics

- Designed for UF300 and UF200SA production line application
- With ATEN [KA7174](#) and RCM series multi-port products (such as [RCM816](#)), the RCMA200SA can easily access from local console and over IP remote console
- Supports virtual keyboard for easy operation
- Firmware upgradable

**Especificaciones**

Conectores	
Puertos de consola	1 x Custom 60-pin Connector (Black)
Puertos KVM	1 x Custom 60-pin Connector (Black)
Alimentación	1 x DC Jack (Black)
RS-232	1 x DB-9 Male (Black)
LEDs	
Alimentación	1 (Green)
Consumo de energía	DC5V:0.38W:2BTU/h  Nota: ● La medición en vatios indica el consumo de energía típico del aparato sin carga externa. ● La medición en BTU/h indica el consumo de energía del dispositivo cuando está totalmente cargado.
Condiciones medioambientales	
Temperatura de funcionamiento	0 - 50°C
Temperatura de almacenamiento	-20 - 60°C
Humedad	0–80% RH, Non-condensing
Propiedades físicas	
Carcasa	Metal
Peso	0.31 kg ( 0.68 lb )
Dimensiones (LA x AN x AL)	12.80 x 8.16 x 2.50 cm (5.04 x 3.21 x 0.98 in.)
Nota	Tenga en cuenta que, en algunos productos de montaje en bastidor, las dimensiones físicas estándar de anchura x profundidad x altura se expresan en el formato longitud x anchura x altura.

Diagrama



**ATEN International Co., Ltd.**

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.