

## CS9134

4-Port PS/2 VGA KVM Switch



CS9134 is a KVM Switch with built-in PS/2. It can control 4 servers via a single console and allows users to switch between computers via the buttons on the front panel of the switch or the hotkey configuration on the console keyboard. It is the simplest and most convenient most convenient solution for multi-computer management. Moreover, it supports 3-tier connection via cascade. With 21 sets of CS9134, users can control 64 computers.

### Features

- One PS/2 console controls 4 computers.
- Cascadable up to 3 levels - provides up to 64 computers.
- Computer selection via front panel pushbuttons, hotkeys or On Screen Display (OSD).
- Keyboard and mouse emulation for error free booting.
- Supports Microsoft IntelliMouse, Logitech MouseMan, FirstMouse, IBM Scrollpoint Mouse.
- OSD automatically adjusts to resolution changes.
- Auto Scan function to monitor computer operation.
- Superior video quality: up to 1920 x 1440; DDC2B.
- Available in silver and black.
- Special design for easy stacking.
- Rack mountable in 19" (1U) system rack.
- Multiplatform support: Windows 2000/XP/Vista, Linux and FreeBSD.
- For more information about KVMs which can connect to CS9134, see [Compatible KVM Table](#).

### Specifications

Computer Connections	
Direct	4
Maximum	64 (via Cascade)
Port Selection	OSD, Hotkey, Pushbutton
Connectors	
Console Ports	1 x HDB-15 Female (Blue) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green)
KVM Ports	4 x HDB-15 Male (Blue) 4 x 6-pin Mini-DIN Female (Purple) 4 x 6-pin Mini-DIN Female (Green)

Power	1 x DC Jack (Black)
Switches	
Power	4 x Pushbutton
LEDs	
Online	4 (Green)
Selected	4 (Orange)
Power	1 (Blue)
Emulation	
Keyboard / Mouse	PS/2
Video	1920 x 1440; DDC2B
Scan Interval	3 ,5, 10, 15, 20, 30, 40, 60 seconds
Power Consumption	DC9V: 2.07w:10BTU/h  Note: <ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul>
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20-60°C
Humidity	0-80% RH, Non-condensing
Physical Properties	
Housing	Metal
Weight	2.55 kg ( 5.62 lb )
Dimensions (L x W x H)	43.72 x 16.29 x 4.40 cm (17.21 x 6.41 x 1.73 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.