


## RC1800

42U Network/Server Rack with Perforated Front and Rear Doors



## Modernized Rack Build for Critical IT Assets




**RC1800**

42U Network/Server Rack with  
Perforated Front and Rear Doors

Reputable for their sturdiness and reliability, ATEN racks are accredited with various certifications to demonstrate their reliability in securing critical IT equipment within data centers and server rooms. In addition to UL and CE certifications, ATEN racks are also EIA/ECA-310-E compliant.

The intelligent industrial design of the rack also yields higher energy savings and reduced carbon emissions, further promoting ESG efforts.



### 3-Axis Rack Frame for Sturdy and Secure Build

The heavy-duty construction along the XYZ axis supplies the robustness required to form the frame of the rack and the requisite sturdiness.

### Intelligent Design of Quick Release Side Panels

Advanced industrial design ensures simple and effortless installation and safety measures in place to protect the installer's safety, and easy cabling.



**Perforated Front and Rear Doors for Optimized Airflow Management**

The perforated design for the front and rear doors improves rack airflow and energy efficiency, generating a ventilation rate that exceeds 66%. The advanced cooling design aligns perfectly with contemporary carbon reduction and energy conservation demands.

**Modularized Plates for Top and Bottom Covers for Customized Needs**

Both the top and bottom covers have modularized plates that can be re-arranged based on your deployment needs. Optional fan modules can also be added and placed based on cable positioning.



**Flexible Cable Management**

The plastic finger duct cable manager located on the side secures the cables to ensure they are organized and safely protects cables from potential deterioration and breakage.

**Applications**

Whether it be server rooms or data centers, the server rack can be counted on to secure your most valuable assets.

## Server Room



## Data Center



**Talk to Our Experts**

If you prefer to have ATEN contact you, please complete the form and a representative will be in touch with you shortly

|                   |                                                                                     |
|-------------------|-------------------------------------------------------------------------------------|
| First Name *      |                                                                                     |
| Last Name *       |                                                                                     |
| - Country *       |  |
| Company *         |                                                                                     |
| Email *           |                                                                                     |
| Phone Number *    |                                                                                     |
| - Customer Type * |  |
| Job Title *       |                                                                                     |

## Features

With more than 30 years of experience in R&D and manufacturing cabinet products, ATEN can tailor exclusive products for its customers based on their needs. Our cabinet products, all of which are extremely popular, have been certified by UL and by CE. All ATEN's rack products are EIA/ECA-310-E compliant. Our high-quality cabinets have multiple patents numbered: M377678, M385174, and M513193.

All ATEN's network/server racks are designed for energy saving and carbon reduction, all of which feature heavy-duty construction, intelligent design, safety, and robustness. ATEN rack solutions are ideal for any kinds of data center builds and their cable management.

- Heavy-duty Construction

- The frame of the rack consists of three parts: extruded 6063 T5 aluminum columns, beams and beam-to-column connections that are made of aluminum-alloy ( ADC12 ) with t-shaped brackets. For added robustness, beams and columns are connected to beam-to-column connection by M8 screws
- Static loading capacity up to 1800kg and dynamic loading capacity up to 1000kg
- Certified MIL-STD-167/MIL-STD-810G vibration test (Military Standard)
- Certified GR-63-CORE Zone4 seismic test (Equivalent to earthquake of magnitude eight)
- All ATEN's standard rack products are EIA/ECA-310-E compliant
- Adjustable mounting rails are made from cold-rolled steel (SPCC). The materials are triple bent so as to enhance its loading capacity

- Airflow Management

- The components of the structure are designed for ergonomics with high-precision quality and for optimizing airflow management to conserve energy and reduce carbon emissions
- Perforated doors for massive front-to-rear airflow provide a ventilation rate above 66%. (The distance cross the corners of the hexagonal mesh is 2mm, and the length of its side is 5mm.)
- Quick-release side panels offer simple and effortless installation
- Multi-module fan unit (2-fan unit / 4-fan unit/ 6-fan unit) can effectively manage the hot air from operating equipment. These are UL compliant and can help increase electrical safety

- **Intelligent Design**

- Multi-stage quick-release top and bottom covers allow cables to easily pass through the rack
- U positions are numbered on adjustable mounting rails to help IT experts recognize the position to quickly install equipment
- M16 leveling feet secure the racks in place by adjusting the leveling feet even if the racks are set up in a server room with non-raised floors
- Lifting eye-bolts (M16 thread) at the top of the rack, which can be used to hang and move the rack when an elevator is not available
- The high-strength horizontal support rails can disperse the weight of IT equipment, making the racks robust and safe
- Anti-seismic connection design (such as side baying connectors or top baying connectors) offers safe connections in between racks and in between racks and the building

- **Certifications**

- UL Certified and CE Certified
- Compatible with the latest specification of EIA/ECA-310-E
- Certified MIL-STD-167/MIL-STD-810G vibration test (Military Standard)
- Certified GR-63-CORE Zone4 seismic test ( Equivalent to earthquake of magnitude eight)
- Qualified for a static load test of 1800kg

- **Includes**

- Server rack enclosure frame × 1 pc
- Perforated front and rear doors with aluminum frame (with door lock and keys) × 2 pcs
- Removable upper and lower side panels × 2 sets
- Roof and floor panels × 1 set
- Caster × 4 pcs
- Leveling feet × 4 pcs
- M5 Mounting Screw × 50 pcs
- Cage nut × 80 pcs

\*For more rack door type available to the rack, please refer to the data sheet

## Specifications

| Function                         | RC1800                                                                        | RC1801                                                                        | RC1802                                                                        |
|----------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| Physical Properties              |                                                                               |                                                                               |                                                                               |
| Rack Height (U Spaces)           | 42U                                                                           | 42U                                                                           | 42U                                                                           |
| Internal Height                  | 1869 mm                                                                       | 1869 mm                                                                       | 1869 mm                                                                       |
| Overall Height, Casters Included | 2045 mm                                                                       | 2045 mm                                                                       | 2045 mm                                                                       |
| Overall Height, Casters excluded | 1965 mm                                                                       | 1965 mm                                                                       | 1965 mm                                                                       |
| Overall Depth                    | 1000 mm                                                                       | 1100 mm                                                                       | 1200 mm                                                                       |
| Overall Width                    | 800 mm                                                                        | 800 mm                                                                        | 800 mm                                                                        |
| Color                            | Black (RC1800B) / White (RC1800W)                                             | Black (RC1801B) / White (RC1801W)                                             | Black (RC1802B)/ White (RC1802W)                                              |
| Enclosure Frame                  | AL 6063T5                                                                     | AL 6063T5                                                                     | AL 6063T5                                                                     |
| 19" EIA Rails                    | SPCC / SPHC                                                                   | SPCC / SPHC                                                                   | SPCC / SPHC                                                                   |
| Roof and Floor Panels            | SPCC / SPHC                                                                   | SPCC / SPHC                                                                   | SPCC / SPHC                                                                   |
| Door Type                        | Perforated Front Door with Alu. Frame<br>Perforated Rear Door with Alu. Frame | Perforated Front Door with Alu. Frame<br>Perforated Rear Door with Alu. Frame | Perforated Front Door with Alu. Frame<br>Perforated Rear Door with Alu. Frame |
| Side Panel Type                  | Lockable Side Panels - Split                                                  | Lockable Side Panels - Split                                                  | Lockable Side Panels - Split                                                  |
| Weight Loading (Static)          | 1800 kg                                                                       | 1800 kg                                                                       | 1800 kg                                                                       |
| Weight Loading (Dynamic)         | 1000 kg                                                                       | 1000 kg                                                                       | 1000 kg                                                                       |

### ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.