


## IC320U

2-Port USB 3.0 PCI-e Card



ATEN IC320 is a 2-port USB 3.0 PCI-e Card, which supports USB 3.0 Super-Speed devices. It provides speeds of up to 10x faster than that of USB 2.0, enabling you to access and transfer your data much faster simply by adding two USB 3.0 ports to your PCI Express-capable PC. It is backwards compatible with USB 2.0 and USB 1.1, ensuring compatibility with existing devices. The new USB 3.0 standard supports transfer rates of up to 5 Gb per second. You can back up large volumes of data, such as high definition videos and high resolution photos, to an external USB 3.0 drive quickly within a short amount of time. In addition, the IC320 2-Port USB 3.0 PCI-e Card also supplies 900mA of power per USB port, allowing more external devices to operate without the need of an additional power source.




### Features

- Adds 2 downstream ports on your system
- Fully complies with USB 3.0 specifications
- Conforms to PCI Express Base Specification 2.0
- Backwards compatible with USB 1.1 and 2.0 devices
- USB-IF certified

## Specifications

|                        |                                                                                                                                 |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Connectors             |                                                                                                                                 |
| USB Port               | 2 x USB 3.0 Type A                                                                                                              |
| LEDs                   | 2 (Green)                                                                                                                       |
| Maximum Transfer Rate  | 5 Gbps                                                                                                                          |
| Maximum Current        | 900 mA per port                                                                                                                 |
| Environmental          |                                                                                                                                 |
| Operating Temperature  | 0-50°C                                                                                                                          |
| Storage Temperature    | -20-60°C                                                                                                                        |
| Humidity               | 0-80% RH, Non-condensing                                                                                                        |
| Physical Properties    |                                                                                                                                 |
| Housing                | Plastic, Metal                                                                                                                  |
| Weight                 | 42 g                                                                                                                            |
| Dimensions (L x W x H) | 12.10 x 0.83 x 0.22 cm                                                                                                          |
| Note                   | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

## Diagram



### **ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their  
 respective owners.