

## UC1284B

USB to IEEE1284 Printer Adapter (1.8m)



UC1284B is a USB to parallel port converter. It converts the USB on PCs, notebook PCs and handheld computing devices into a parallel port for printer connection.



**Bus-  
Powered**



**Easy  
Installation**

### Features

- Fully bidirectional to ensure compatibility with today's latest printers
- 1 USB Type-A connector for standard USB cable connection
- 1 C-36 parallel connector
- Fully compliant with USB
- Non-powered
- Max. Throughput: 1.2 Mbits/ Sec (ECP Mode)
- OS Support: Windows 2000, Windows XP, Windows Vista and Windows 7

## Specification

|                        |                                                                                                                                                                                                                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connectors             |                                                                                                                                                                                                                                                                                                           |
| USB Port               | 1 x USB Type A Male (White)                                                                                                                                                                                                                                                                               |
| Printer                | 1 x C-36 Male                                                                                                                                                                                                                                                                                             |
| Data Rate              | 1.2 Mbits/Sec                                                                                                                                                                                                                                                                                             |
| Cable Length           | 1.8m                                                                                                                                                                                                                                                                                                      |
| LEDs                   | N/A                                                                                                                                                                                                                                                                                                       |
| Power Mode             | Bus Powered                                                                                                                                                                                                                                                                                               |
| USB Specification      | USB compliant                                                                                                                                                                                                                                                                                             |
| Environmental          |                                                                                                                                                                                                                                                                                                           |
| Operating Temperature  | 0-40°C                                                                                                                                                                                                                                                                                                    |
| Storage Temperature    | -20-60°C                                                                                                                                                                                                                                                                                                  |
| Humidity               | 0-80% RH, Non-condensing                                                                                                                                                                                                                                                                                  |
| Physical Properties    |                                                                                                                                                                                                                                                                                                           |
| Housing                | Plastic                                                                                                                                                                                                                                                                                                   |
| Weight                 | 0.11 kg ( 0.24 lb )                                                                                                                                                                                                                                                                                       |
| Dimensions (L x W x H) | 5.30 x 4.30 x 1.95 cm<br>(2.09 x 1.69 x 0.77 in.)                                                                                                                                                                                                                                                         |
| Power Consumption      | DC5V:0.1W:11BTU/h<br><br>Note:<br><ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul> |
| Note                   | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.                                                                                                                                                                           |

**Diagram****ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.