


## IC-102S

RS-232 2 Port PCI card



RS232 converters and extenders are heavily represented in many enterprise fields. • The telecommunication industry • Auto-teller machines • Airport check-in and flight schedule display systems • Automatic postal machines • Power and energy distribution monitoring and control systems • Highway tunnel monitoring and traffic lights • Building automation from remote image transmission to elevator control

### Features

- Fully compliant with PCI Spec. Ver2.2 standard.
- Supports both 64-bit & 32-bit PCI Bus and 3.3V & 5V connector keys.
- High speed serial port support baud rates up to 921.6Kbps.
- High-tech 128K FIFO can reduce CPU loading, interrupting and improving system performance dramatically.
- Plug and Play, I/O address and IRQ assigned by BIOS.
- Works with various type of DB9M / DB25M serial devices.
- Ready for the Intel® Itanium® and AMD® Athlon® 64R 64-bit CPU on the Microsoft Windows® XP 64-bit Edition Version 2003 and Windows® Sever 2003 for 64-bit Itanium-based or Extended Systems.
- Ideal for 56K V.90 external modems and ISDN terminal adapters, PDA, UPS, barcode scanner and other high-speed serial port devices.
- OS Support: Windows 2000, Windows XP and Linux

## Specifications

|                       |                                                    |
|-----------------------|----------------------------------------------------|
| Mode of Operation     | Hand-shaking Mode                                  |
| Bus Transceivers      | RS-232 Full-duplex                                 |
| Drivers per Line      | RS-232 1 Driver                                    |
| Receivers per Line    | RS-232 1 Receiver                                  |
| Hardware              |                                                    |
| Controller            | UART (16C650 compatible)                           |
| Bus Interface         | 64-bit & 32-bit PCI Bus - 3.3V & 5V Connector Keys |
| Connector             | 2 DB9 Male                                         |
| Communication         |                                                    |
| IRQ & I/O Address     | Assigned by BIOS                                   |
| FIFO                  | 32 bytes hardware FIFO                             |
| Baud Rate             | 75bps ~921.6Kbps                                   |
| Data Bit              | 4, 5, 6, 7, 8                                      |
| Stop Bit              | 1, 1.5, 2                                          |
| Parity                | even, odd, none, mark, space                       |
| Flow Control          | None, Xon/Xoff, Hardware                           |
| Signals               | DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI         |
| Driver Supported      |                                                    |
| 64-bit System         | Intel Itanium and AMD Athlon64 CPU                 |
| Microsoft             | DOS, Windows 3.x / 9x / ME / NT / 2000 / XP / 2003 |
| Linux                 | 2.0.x / 2.2.x / 2.4.18 / 2.4.20                    |
| DOS                   | DOS                                                |
| Environmental         |                                                    |
| Operating Temperature | 0 - 57°C                                           |
| Storage Temperature   | -20 - 85°C                                         |
| Humidity              | 5 ~ 95% RH                                         |

### ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.