

KA9250

PS/2 VGA Console Extender (Console Module for the KH0116)



The KA9250 KVM Extender Module allows a user at a keyboard, video, mouse (KVM) console to manage the servers in a [KH0116](#) 16 Port High-Density KVM Switch installation up to 150m away. The KA9250 module connects to the [KH0116](#)'s RJ-45 remote console port via standard Category 5 cable for a neat and reliable installation. When a local and remote console are present, both can access the KVM switch.

The KA9250 features a custom ASIC to ensure the utmost in reliability and compatibility. It can also sense the distance to the [KH0116](#) and automatically adjust the video gain to compensate. Control your KVM switch from up to 150m away by extending the distance to your KVM console with a KA9250 KVM Extender.

Features

- Built-in ASIC for greater reliability and compatibility
- Cat 5e cable to connect the remote unit to the [KH0116](#) up to 150m away
- High resolution video-up to 1280 x 1024 (SXGA)
- Supports VGA, SVGA, and MultiSync monitors
- Automatic gain control-adjusts signal strength to compensate for distance
- Multiplatform support: Windows 2000/XP/[Vista](#).

Specifications

| | |
|------------------------|---|
| Connectors | |
| Link | 1 x RJ-45 Female (Black) |
| Computer | 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x HDB-15 Female (Blue) |
| LEDs | |
| Online | 1 (Green) |
| Power | 1 (Orange) |
| Video | 1280 x 1024 |
| Cable Length | 150m |
| Power Consumption | AC 9V 4.0W (max.) Note: <ul style="list-style-type: none"> ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded. |
| Environmental | |
| Operating Temperature | 0 ~50°C |
| Storage Temperature | -20 ~60°C |
| Humidity | 0 ~ 80% RH, Non-condensing |
| Physical Properties | |
| Housing | Metal |
| Weight | 0.22 kg |
| Dimensions (L x W x H) | 10.10 x 8.68 x 3.88 cm |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their
respective owners.