

## KA7175

USB VGA Virtual Media KVM Adapter



The KA7175 USB Virtual Media KVM Adapter Cable connects the KVM switch to the video and USB ports of the target computer. With its small form factor and light weight design, it represents the next generation of USB Virtual Media KVM Adapter Cables - offering superior signal compensation and delay skew techniques for greatly enhanced video quality.

### Features


- Auto Signal Compensation (ASC), no DIP switch setting needed for the different distances
- Keyboard and mouse emulation - keeps your server functioning smoothly when it is disconnected from the switch's KVM port or relocated to different KVM port
- Lifetime firmware upgrades
- Superior video quality - supports resolution up to 1920 x 1200 (Reduced blanking)\*
- Built in ASIC for greater reliability and compatibility
- Compact size
- Virtual Media Support

\* This maximum resolution may vary depending on the transmission distance. For more details, please refer to the product pages of the connected KVM switches.

## Specifications

|                        |                                                                                                                                 |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Connectors             |                                                                                                                                 |
| Link                   | 1 x RJ-45 Female                                                                                                                |
| Computer               | 1 x USB Type A Male<br>1 x HDB-15 Male                                                                                          |
| LEDs                   |                                                                                                                                 |
| Online                 | 1 (Green)                                                                                                                       |
| Power                  | 1 (Orange)                                                                                                                      |
| Environmental          |                                                                                                                                 |
| Operating Temperature  | 0–50°C                                                                                                                          |
| Storage Temperature    | -20–60°C                                                                                                                        |
| Physical Properties    |                                                                                                                                 |
| Housing                | Plastic                                                                                                                         |
| Weight                 | 0.15 kg ( 0.33 lb )                                                                                                             |
| Dimensions (L x W x H) | 9.00 x 4.30 x 2.18 cm<br>(3.54 x 1.69 x 0.86 in.)                                                                               |
| Note                   | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

## Diagram



### **ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their  
 respective owners.